

UCO BANK					
NAME OF WORKS: PROPOSED INTERIOR DESIGN FOR ATHWALINES BRANCH, GHOD-DOD RD., SURAT.					
PART-01-INTERIOR FURNITURE WORK BOQ					
Note: Contractor need to Quote for Zero Qty. item also.					
Sr. No.	DISCRIPATION	QTY.	PER	RATE	AMOUNT
1	<p><b>Providing &amp; Fixing of Armstrong Mineral Fibre Acoustical Suspended Ceiling System</b> with Classic Lite Beveled Tegular Edge Tiles With Armstrong Suprafine 15mm Exposed GRID. The tiles should have Humidity Resistance (RH) of 95%, NRC 0.5, Light Reflectance ≥80%, Thermal Conductivity k = 0.052 - 0.057 w/m K, Colour White, Fire Performance UK Class 0 / Class 1 (BS 476 pt - 6 &amp;7) in module size of 600 x 600 x 15mm , suitable for Green Building application, with Recycled content of 32%.</p> <p>The tile shall be laid on Armstrong Suprafine 32 with 15 mm wide T - section flanges colour white having rotary stitching on all T sections i.e. the Main Runner, 1200 mm &amp; 600 mm Cross Tees with a web height of 32mm and a load carrying capacity of 7.5 Kgs/M2 (as per standard installation layout mentioned below) &amp; pull out strength of minimum 100 Kgs.. The T Sections have a Galvanizing of 90 grams per M2 and need to be installed with Suspension system of Armstrong make.</p> <p>INSTALLATION: To comprise main runner spaced at 1200mm securely fixed to the structural soffit using Armstrong suspension system (specifications below) at 1200mm maximum. The First/Last Armstrong suspension system at the end of each main runner should not be greater than 450mm from the adjacent wall.</p> <p>Flush fitting 1200mm long cross tees to be interlocked between main runners at 600mm to form 1200 x 600 mm module. Cut cross tees longer than 600mm require independent support. 600 x 600mm module to be formed by fitting 600mm long flush fitting cross tees centrally between the 1200 mm cross tees.</p> <p>Perimeter trim to be Armstrong wall angles of size 3000x19x19mm, secured to walls at 450 mm maximum.</p> <p>Installation to be carried out by Armstrong Trained Installation team &amp; Installation should be carried out as per Armstrong recommended procedure.</p> <p>ARMSTRONG SUSPENSION SYSTEM accessories manufactured and supplied by Armstrong World Industries consisting of M6 Anchor Fasteners with hanger hole, pre Straightened Hanger wire of dia – 2.5 mm of 1.80 m length having a tensile strength of 344-413 MPa and a minimum pull strength of 110 kgs. (Adjustable hook clips of 0.7mm thick, galvanized spring steel can also be used for installation purpose as an additional accessory. The adjustable clip also consists of a 4 mm aquiline wire to be used with the main runner).</p>	431.00	Sq.Ft.		
2	<p><b>FALSE CEILING</b> Pro. And fixing single layer water proof gypsum board 12.5 mm thick sections using water proof board of size 1220 mm x 1830 mm x 8.0 mm suspended by GI suspender channel of size 25 mm x 3 mm with intermediate channel og size 18 mm x 40 mm x 0.8 mm at 1220 mm center to center ceiling section of size 40 mm x 35 mm x 0.55 mm at 457 mm c/c and perimeter channel A of size 20 mm x 27 mm x 30 mm x 0.5 mm at edges &amp; drops incl.paper tap sand sofit cleat, anchor fastener, scoch bolt connecting cleat,joining compound top coat on ceiling incl.making necy.opening for light fitting,diffuser etc. comp. as per detail drawing as directed.</p>	466.00	Sq.Ft.		

3	<p><b>SOLID PARTITION: Approx 3" Thk / 75 mm Thk</b>          Providing and fixing in position solid Full height partition in frame work including door in 2' X 2' grid (horizontally and vertically) comprising of 2" X 1" Alu. section (Zindal, Tata steel or equivalent) with <b>8 mm thick Commercial Plywood</b> on both sides finished with <b>1mm thick laminates</b> of approved make and colour. Item to include Alu. section for door frame. All exposed T.W. surfaces to be finished in polish of matching laminate colour as directed including all necessary Stainless steel finish fittings/ hardware, door closers, locks and wood preservative paint etc. as per list of approved material and as approved by the Project Consultant / Bank complete in all respects.</p> <p>(Note : In case of false ceiling, the vertical Alu. Section to be fixed with pucca ceiling but the area of partition payable will be below the false ceiling only) Rate is inclusive of 35 mm thk Flush door and other door accessories, etc... complete.</p> <p>Ply: Commercial- Century, Archid, GREENPLY only...</p> <p>All accessories &amp; Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma.</p> <p>Exterior / Outside Laminate: Royal Touch, Century, Green lam, MERINO only.</p> <p>Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.</p> <p><b>Handle: 'F' Profile black anodised Alu. handle.</b></p> <p><b>All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish.</b></p>	0.00	Sq.Ft.		
4	<p><b>PARTLY GLAZED FULL HEIGHT PARTITION WITH DOOR- Approx 3" / 75 mm thk</b>          Providing and fixing in position partly glazed full height partition work including door in frame work at 2' X 2' grid (horizontally and vertically) comprising of 2" X 1" Alu. section (Zindal, Tata steel or equivalent) with <b>8 mm thick Commercial Plywood</b> on both sides finished with <b>1mm thick laminates of approved make and colour</b>. Item to include Alu. section for door frame. Item to include <b>10 mm thick toughned glass</b> with etching and frosting as per design to be fixed with 1-1/4" x 3/4" Tk. Wd. moulding finished with French polish as directed. Extra aluminium section to be fixed on periphery of glass &amp; Door. All exposed T.W. surfaces to be finished in polish of matching laminate colour as directed. This item includes all necessary Stainless Steel finish fittings / hardware, Brass hinges, SS Screws, door closers, locks and wood preservative paint etc. as per list of approved material and as approved by the Project consultant / bank complete in all respects.</p> <p>(Note : In case of false ceiling, the vertical Alu. members to be fixed with pucca ceiling but the area of partition payable will be below the false ceiling only).</p> <p><b>Door Shutter: Min. 35 mm thk Tk. Wood Door with 10 mm thk Toughned Glass panel. Shutter should be finished with 1mm thick laminates of approved make and colour on both sides along with approved make Door Handles, Lock with handle &amp; min. 3/4 keys, conceal door stopper of approved make incl. of all fitting &amp; complete.</b></p> <p>Ply: Commercial- Century, Archid, GREENPLY only...</p> <p>All accessories &amp; Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma.</p> <p>Exterior / Outside Laminate: Royal Touch, Century, Green lam, MERINO only.</p> <p>Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.</p> <p><b>Handle: S.S. 2' ht round handle (both side)</b></p> <p><b>Lock: Glass to Partition / Flooring / Wall SS Lock.</b></p> <p><b>Rate is inclusive of 35 mm thk Flush door and other door accessories, etc... complete.</b></p> <p><b>All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish.</b></p> <p><b>@ Low Ht. Partition between 2 tables: 12/15/18 mm thk soft board with faabric cover to be provided above table ht. as per design.</b></p>	536.20	Sq.Ft.		
5	<p><b>Providing &amp; Fixing 12mm thick Toughened Glass Doors WITH Glass door Lock of Saint-gobain, Modi or equivalent company.</b></p>	56.00	Sq.Ft.		
6	<p><b>Providing &amp; Fixing SS Floorspring (Dorma, Hettich, Enox, Ebco or equivalent)</b> Floor spring for single-leaf single action / double action swing door. Installation in the floor.</p> <p>High quality cast iron mechanism body.</p> <p>Provided with door stop function and explosion proof device. Suitable for wooden, glass and alu etc. Maximum. door opening angle in each direction : 130°.</p> <p>Controllable closing angle: 90° +15° -0°.</p> <p>he width inside the frame can be adjusted by 10 mm, length by 7 mm and height 4 mm.</p> <p>Tested-500,000 Cycles, Cover plate finish: Satin Stainless Steel.</p> <p><b>105 / 120 Kg.</b></p>	2.00	Nos.		
7	<p><b>Cutting Hole in 12 mm thk. Glass for Handle, Floor spring or any other patch fittings. (Only cutting labour is included, no Glass material cost)</b></p>	8.00	Nos.		

8	Providing & Fixing 600 mm height SS handle ( <b>Dorma, Euro, Ozone, Enox, Ebco, Hamco or equivalent</b> ) both side of glass.	2.00	Pair		
9	Providing and fixing 35 mm thick Flush Door shutters ( <b>Make: Century, Kitply, Green Ply, Anchor, Orchid or equivalent company</b> ) including SS suitable hinges with necessary screws, etc... with 1.0 mm thk exterior type laminate of <b>Archidlam National, Formica, Green lam, MERINO Or Equivalent</b> company on both side of flush door, S.S. / Brass premium quality Mortice Handle with lock body with min. 4 no. of keys. Mortice Handle with lock body should be of <b>Godrej, Haffle, Hettich, Ebco or equivalent</b> company make. (For toilet door one outside to be finish with 1.0 mm laminate & one inside to be finish with 1 to 1.5 mm PVC sheet.)	0.00	Sq.Ft.		
10	<b>Frosted Film on Glass Surface:</b> Providing and fixing frosted film to be installed on glazed partition as per design or bank's instruction of <b>3M or equivalent company make</b> . This item includes cutting, pasting & proper finishing, etc... complete.	264.30	Sq.Ft.		
11	Providing and fixing in Full Ht. storage <b>600 mm Depth</b> as per drawing including Drawer storage (Belowit) by using 18,12,10 mm thick Commercial Plywood & laminate. All exposed exterior Commercial Plywood of table shall be finished with 1mm thick good quality laminates of approved make and shades as shown in the drawing and all other inside faces shall be finished with inside 1 mm thk. laminates of approved shade. All ply edges to be protected with 1/2" thk. beading patti and beading patti to be finished with french polish. <b>2 Nos. Drawer units below 2 shutters</b> as per drawing shall be provided with Godrej locks in drawer. Drawer unit shall be finished with 1mm thick good quality laminates of approved make. all inside shall be finished with inside 0.9/1 mm thk. laminates of approved shead. All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish. The drawers will be provided with handles (Stainless steel finish) and telescopic channels as per approval of the Project Consultant / Bank.  <b>The shutter shall be fixed with S.S. 'Z' hinges. Inside of shutter storage space 6 mm S.S.(304) solid rod to be place @ 100-125 mm C/C for file storage in layers- front side &amp; back side (2 Rows).</b>  Ply: Commercial- Century, Archid, GREENPLY only... All accessories & Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma. Laminate: Royal Touch, Century, Green lam, MERINO only. Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.	43.80	Sq.Ft.		
12	<b>Providing and fixing in Full Ht. storage 450 mm Depth</b> as per drawing including Drawer storage (Belowit) by using 18,12,10 mm thick Commercial Plywood & laminate. All exposed exterior Commercial Plywood of table shall be finished with 1mm thick good quality laminates of approved make and shades as shown in the drawing and all other inside faces shall be finished with inside 1 mm thk. laminates of approved shade. All ply edges to be protected with 1/2" thk. beading patti and beading patti to be finished with french polish. <b>2 Nos. Drawer units below 2 shutters</b> as per drawing shall be provided with Godrej locks in drawer. Drawer unit shall be finished with 1mm thick good quality laminates of approved make. all inside shall be finished with inside 0.9/1 mm thk. laminates of approved shead. All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish. The drawers will be provided with handles (Stainless steel finish) and telescopic channels as per approval of the Project Consultant / Bank.  <b>The shutter shall be fixed with S.S. 'Z' hinges. Inside of shutter storage space 6 mm S.S.(304) solid rod to be place @ 100-125 mm C/C for file storage in layers- front side &amp; back side (2 Rows).</b>  Ply: Commercial- Century, Archid, GREENPLY only... All accessories & Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma. Laminate: Royal Touch, Century, Green lam, MERINO only. Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.	344.60	Sq.Ft.		

13	<p>Providing and fixing in <b>Low Ht. storage 450 mm Depth</b> as per drawing including Drawer storage (Below it) by using 18,12,10 mm thick Commercial Plywood &amp; laminate. All exposed exterior Commercial Plywood of table shall be finished with 1mm thick good quality laminates of approved make and shades as shown in the drawing and all other inside faces shall be finished with inside 1 mm thk. laminates of approved shade. All ply edges to be protected with 1/2" thk. beading patti and beading patti to be finished with french polish.</p> <p><b>2 Nos. Drawer units below 2 shutters</b> as per drawing shall be provided with Godrej locks in drawer. Drawer unit shall be finished with 1mm thick good quality laminates of approved make. all inside shall be finished with inside 0.9/1 mm thk. laminates of approved shade. All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish. The drawers will be provided with handles (Stainless steel finish) and telescopic channels as per approval of the Project Consultant / Bank.</p> <p><b>The shutter shall be fixed with S.S. 'Z' hinges. Inside of shutter storage space 6 mm S.S.(304) solid rod to be place @ 100-125 mm C/C for file storage in layers- front side &amp; back side (2 Rows).</b></p> <p>Ply: Commercial- Century, Archid, GREENPLY only...</p> <p>All accessories &amp; Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma.</p> <p>Laminate: Royal Touch, Century, Green lam, MERINO only.</p> <p>Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.</p>	7.40	Sq.Ft.		
14	<p>Providing and fixing in Over Head storage <b>450 mm Depth</b> unit as per drawing including Drawer storage (Below it) by using 18, 12, 09 mm thick Commercial Plywood &amp; laminate. All exposed exterior Commercial Plywood of table shall be finished with 1mm thick good quality laminates of approved make and shades as shown in the drawing and all other inside faces shall be finished with inside 1 mm thk. laminates of approved shade.</p> <p><b>The shutter shall be fixed with S.S. 'Z' hinges. Inside of shutter storage space 6 mm S.S.(304) solid rod to be place @ 100-125 mm C/C for file storage in layers- front side &amp; back side (2 Rows).</b></p> <p>Ply: Commercial- Century, Archid, GREENPLY only...</p> <p>All accessories &amp; Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma.</p> <p>Exterior / Outside Laminate: Royal Touch, Century, Green lam, MERINO only.</p> <p>Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.</p> <p><b>Handle: 'F' Profile black anodised Alu. handle.</b></p> <p><b>All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish.</b></p>	38.62	Sq.Ft.		
15	<p>Providing &amp; fixing 12 mm thick Soft Board covered with wooven fabric (make of Response) of good quality. Fabric to be fix with proper sinthetic adhesive/ non rusting metal clips on back side of the soft board. No stiches to seen on face side. The whole soft board to be fix on 12 mm thk Commercial Plywood vertical surface with the help of S.S. screws with cap/ botton screw or SS strud. All included...</p>	54.30	Sq.Ft.		
16	<p>Providing and fixing <b>Roller blinds (vista, peritex, winfab, mac or equivalent compnay)</b> as per the approved design and shade including standard fitting as per the manufacturer's specifications.</p>	90.00	Sq.Ft.		

	<p><b>Providing and fixing in position Officer / Staff table / Counters as per Banks standard brand image with 1.0mm tk. LAMINATES in one/two shades to be used as per design provided by Bank/Architect. Table shall be of independent type like modular furniture with individual side legs Shape as per design.</b></p> <p><b>Table:</b> shall consist of 18mm thk. Commercial Grade Ply top, aprons &amp; verticals with necessary pattern, grooves &amp; shade. Foot rest of 1 1/2" x 3" T.W members &amp; Cable manager shall provided. The Table top, Front Apron &amp; Leg Sides should be finished with 1.0mm tk. LAMINATES &amp; all Invisible/Internal surfaces shall be finished 0.8mm LINER of approved shade as directed. At the external sides of top &amp; Side legs will be 36mm of thickness.</p> <p><b>CPU trolley</b> (steel with Nylon Castor): Ready made fixed with telescopic / double (Hafele / Ebco / solo make) approved sliders)</p> <p><b>Articulating Keyboard Tray:</b> These shall be made from CRCA steel duly powder coated. It must have built-in slides which shall be screwed to the underside of the worktop. Each tray must have a soft palm rest and a stow-away design of mouse pad mounted underneath it.</p> <p><b>Drawer Unit (Size as per instruction):</b> A drawer unit to be provided with 1 nos. of pencil drawer &amp; <b>3 nos. of drawers shall be provided.</b> Drawer shall consist of 18mm Commercial Grade Ply sides, back and 12mm thk. Ply base. Facia of drawers shall be of 18mm thk. Ply finished in 1.0mm tk. LAMINATES. Each drawer shall slide on a pair of Heavy Duty telescopic drawer sliders (Hafele/ebco OR approve make) full extension type. All complete with Group-Drawer locks Godrej/Ebco Make, 'G' / 'F' / Linear Black Color Anodized Alu. profile handle &amp; other necessary hardwares as directed by Bank/Architect. All Invisible / Internal surfaces shall be finished 0.8mm LINER of approved shade as directed.</p> <p>Rate shall be inclusive of all necessary approved fittings like locks (Godrej make) for drawers and any miscellaneous hardware items. Provision for Electrical Fixtures / fittings as per requirement of Other Vendors shall be done &amp; neatly finishes the same.</p> <p>Table all 4 sides' edge should be finished with min. 30 mm wide and 18 mm thk wooden round (bevelled) border patti and finished with French Polish along with P.U. Brush finish.</p> <p>File storage to be equiped with 6 mm dia SS rod at every 100 mm c/c front &amp; back side.</p> <p>All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish.</p> <p>All exposed Tk. Wood members to be finished with french polish, unless specified.</p> <p>Outer Laminate make: Royal Touch, Century, Green lam, MERINO only</p>			
17	<p><b>Providing and fixing in Staff Table of size 4'-0" X 2'-0" x 2'-6" as per drawing including 2 Drawers &amp; 1 shutter storage space (Below it).</b> <b>Other Specification as per above mentioned.</b></p>	3	Nos.	
18	<p><b>Providing and fixing in Officer's Table of size 5'-0" X 2'-0" x 2'-6", Side table size of 3'-6" x 1'-6" x 2'-6" as per drawing including 3 nos. of Drawers &amp; storage below it with shutter in 5'-6" length side table (3'-6" + 2'-6" inclusive of 2' wide main table)</b></p> <p>Other Specification as per above mentioned.</p>	4.00	Nos.	
19	<p><b>Providing and fixing in Manager Table of size 6'-9" X 2'-6" X 2'-6" as per drawing including 3 nos. of Drawers &amp; storage below it with shutter.</b></p> <p><b>12 mm thk White BPG with Ultra clear glass shall be place at table top with bevelled / Chamfer / Half Pencil edges all around.</b></p> <p>Side table is not Included in this rate.</p> <p>Other Specification as per above mentioned.</p>	1.00	Nos.	

20	<p>Providing and fixing in <b>Cashier Table</b> of size 5'-9" X 6'-0" X 2'-6" as per drawing including Drawer storage, Shutter storage, etc... as per Bank standard.</p> <p>12 mm White BPG with Ultra clear glass shall be place at table top with bevelled / Chamfer / Half Pencil front edge &amp; crystal finish for other 3 edges all around.</p> <p>Partition wall is not included in this rate.</p> <p>Other Specification as per above mentioned.</p>	1.00	Nos.		
21	<p>Providing &amp; making <b>Wall paneling with 8 mm thk Commercial Plywood &amp; 1.5" x 1" size Alu. Section members at 24" c/c bothways</b> of appropriate thickness &amp; finished with 1mm thick laminate of approved make and shade as specified by Bank etc. complete.</p> <p>Ply: Commercial- Century, Archid, GREENPLY only...</p> <p>All accessories &amp; Hardware: Hettich / Doorset / Enox / Olive / Ebco / Godrej / Dorma.</p> <p>Exterior / Outside Laminate: Royal Touch, Century, Green lam, MERINO only.</p> <p>Synthetic Adhesive: Marine grade Fevicol or Bluecoat of Pedilite company.</p> <p>All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish.</p>	1242.64	Sq.Ft.		
22	<p>Providing and fixing in <b>White Board</b> as per drawing by using 18 mm thick Commercial ply &amp; laminate. Front sides shall be finished with inside mm thk. White color Glossy laminates of approved make. All ply edges to be protect with 1/2" thk. beading patti and beading patti to be finished with french polish. This whole system should have 3/4" x 1.5" size of teak wooden frame on all 4 sides finished with french polish with top seal coat of polymer or synthetic base. This item also includes all necessary accessories, hardwares, etc... complete.</p>	16.00	Sq.Ft.		
23	<p><b>Providing and applying ceiling painting</b> (Min. 2 coats) with Plastic paint of Asian paints or equivalent approved brand and applying on plastered Ceiling surface to give and even shade including thoroughly brushing the surface free from mortor droppings and other foreign matter and sand paperd smooth on new work to give an even shade for all height.</p> <p>+ Applying two coats of Birla or Asian acrylic lapy ( putty) &amp; two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth. This item includes Lapi / Putty, Priming coat &amp; Min. 2 coats of Plastic paint with labour &amp; complete.</p>	466.00	Sq.Ft.		
24	<p><b>Providing and applying Wall painting</b> (three coats) with Royal emulsion paint &amp; Birla or Asian acrylic lapy ( putty) of Asian paints or equivalent approved brand and manufacture on plastered wall surface to give and even shade including thoroughly brushing the surface free from mortor droppings and other foreign matter and sand paperd smooth on new work to give an even shade for all height.</p> <p>+ Applying two coats of Birla or Asian acrylic lapy ( putty) &amp; two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth.</p> <p>This item includes Lapi / Putty, Priming coat &amp; 3 coats of Royal emulsion paint with labour &amp; complete.</p>	73.00	Sq.Ft.		
25	<p>Providing, fabricating &amp; supply of following with upholstered designer <b>multi seater sofa with arm rest on both side and back rest</b> with wooden frame work, no sag springs for seats, sofa made to size, shape &amp; design with 4" thk high density rubber foam of 40 density for seat &amp; 4" thk for back &amp; arm rest covered with 25 mm thk polyfoam &amp; covered with white Markin cloth. Entire sofa to be covered with approved leatherite / fabric all over or at the front with exposed TW/SB band finished with melamine.</p>	0.00	R. Ft.		

26	M.S. Steel work welded in built up sections, framed work including cutting, hoisting, fixing in position and applying a priming coat of red lead paint (A) in beams & joists channels angles, tees, flats with connection plates or angle cleats as in main & cross beams,hip & trussed purlins connected to common raffers & the like.	10.00	Kg.		
27	Painting two coat (excluding priming coat) on new steel and other metal surface with synthetic enamel paint, burshing to give an even shade including cleaning the surface of all dirt, dust and other foreign matters.	25.00	Sq.Ft.		
28	Providing, fabricating & supply of following with upholstered designer bench with arm rest on both side without back rest with wooden frame work, no sag springs for seats, shape & design with 4" thk high density foam of 40 density for seat 3" thk foam for arm rest covered with 12mm thk polyfoam & covered with white Markin cloth. Entire seating bench to be covered with approved leatherite / fabric all over or at the front with exposed TW/SB band finished with melamine.	6.00	R. Ft.		
29	Providing and supplying Outer LED back light Acrylic box & GI / Aluminum sheet Sign board of approved design of approved quality as per the design and instructions including LED lights with graphics, etc....	15.00	Sq.Ft.		
30	Providing and supplying 6 MM THK Acrylic UCO Logo of Size: 0.75 mt size proportion along with pasting on wall, finishing, etc... complete.	2.00	Nos.		
Note: Color shade, laminate pattern, other to be follow Bank standard guidelines / design, etc...Items rates are given by the client.					
			TOTAL		
			18% GST=		
			Total Estimated amount Including GST=		
<b>Amount in Word:</b>					
<b>Name of Contractor with Seal &amp; Signature</b>					
<b>Date :</b>		<b>Place :</b>			