

## BOQ OF INTERIOR FURNITURE OF UCO BANK BANKA BRANCH

S.L	ITEM DESCRIPTION	UNIT	QTY	RATE (Rs)	AMOUNT (Rs)
1.0	<p><b><u>WOODEN TABLE FOR MANAGER</u></b></p> <p><b>MANAGER'S TABLE:</b> Providing and Placing Manager Table of L-shaped size (6'-0" X 3'0" &amp; 2'-9" X 1'-6") edged with teakwood beading of 2"x2" (approx) cut to required shape, top of table to have 1.0mm thick laminates and teakwood beading to be polished to required color. Table to have a vertical modesty panel of 19 mm thick blackboard covered with laminates (1.0mm thick) from the outer side and (0.8mm thick) laminates on the inner side including supply and fixing of sliding keyboard of approved make and provision of 1 no. drawer &amp; 1 no file cabinet with lock &amp; all fitting. In all these tables/counters provision shall be made so that the CPU of the computer can be kept under the table and only the monitor shall be visible. Also there shall be neat hole in the tabletop for the wire.</p>	No	1		
2.0	<p><b><u>NOTICE BOARD- SIZE=3'0"X2'0"</u></b></p> <p>Providing &amp; Fixing in position notice board as per drawing and confirming to the following specifications</p> <p><u>Basic Frame Work</u> Well seasoned hard wood section treated with two coats of wood preservatives minimum 0'-2" x 0'-1" at suitable horizontal vertical spacing not exceeding 2'-0" c/c</p> <p><u>Skin Membrane</u> 4 mm thick BWR grade ply wood over which 12 mm thick approved quality soft board clayed with fabric of approved shade and quality</p> <p><u>Edge Molding</u> All free edges shall have polished 2<sup>nd</sup> class teak wood moulds of approved shape (finished 0'-2" x 0'-1" sections) with equal spirit polish in mat finish</p>	No	1		
3.0	<p><b><u>PRINTER TABLE</u></b></p> <p>Providing and fixing printer table made out of approved 19 mm thick BWP ply frame work for side bottom. A</p>				



	pedestal made of 19 mm thick BWP ply wood for sides shelf and bottom and 6 mm thick BWP ply wood of approved make for the back finished with 1 mm thick laminate of approved make and shade and back side shall be provided underneath .Skirting shall be provided in 1 mm thick laminate of approved make and shade. Pedestal/printer table 3'-0" x 2'-6"	No			
4.0	<b><u>GLASS FOR MANAGER TABLE TOP</u></b> Providing and fixing 12 mm thick floating Glass with polished crystal edge finished etc on Manager table top as per direction of Architect Size (6'-0" x 3'-0" x 1 no)	Sft.	18		
5.0	<b><u>WOODEN/COLUMN/WALL PANELLING</u></b>  Wall paneling/column encasing (up to table height) works as per drawing & conforming to the following specification (Quantity/location should be restricted only to the central pillars in Banking Hall or any prime location)	sft	200		



	<p><u>Basic Frame Work:</u> Well seasoned hardwood sections, treated with two coats of wood preservatives, minimum 0'-2" x 0'-1", at suitable horizontal/vertical spacing not exceeding 2'-0" c/c.</p> <p><u>Skin Membrane:</u> 6 mm thick BWR grade plywood with grooves formed as desired as per drawing/instructions</p> <p><u>Finishing :</u> 1 mm thick laminate sheet of same or combination shades as per instructions.</p> <p><u>Skirting :</u> 0'-4" high x 0'-1/2" thick polished 2<sup>nd</sup> class teak wood skirting with NC lacquer finish Quoted rates teak shall include all necessary materials, accessories &amp; labor &amp; also allow provisions for electrical/telephone/computer wiring conduits &amp; switch boxes .(Material for wiring conduits &amp; switch boxes shall separately paid for.) Columns paneling – Wall paneling</p>	Sft.	0		
6.0	<p><b><u>PARTLY GLAZED FULL HEIGHT WOODEN PARTITION WITH DOOR FOR MANAGER CHAMBER</u></b></p> <p>Supplying &amp; erecting full height door partly glazed wooden door for Manager Chamber as per drawing and conforming to the following specifications</p> <p><u>Basic Frame Work</u> Well seasoned Malaysian hard wood section treated with two coats of wood preservatives 2 1/2" x 1 3/4" (minimum) at maximum 2'-0" horizontal or vertical spacing as per site conditions. Vertical Members shall be suitably anchored at floor &amp; ceiling level to ensure rigidity. Exposed frame members in the glazed portions shall be wider spacing (approx 6'-0") or as per instructions Exposed members shall be finished with 1 mm thick laminate sheet of same or combination shade over 12 mm BWR plywood facing including 4 x 6 mm grooves at location as per instructions</p> <p><u>Skin Membrane</u> Opaque portion up to 3'-0" from floor level and from false ceiling from floor level with 2 x 6 mm thick BWR grade plywood on each face. With Groove formed at the top layer as per drawing/ instructions</p> <p><u>Finishing</u> 1 mm thick laminate sheet of same or combination shades as per instructions.</p> <p><u>Skirting</u> 0'-4" high x 0'-1/2" thick polished teak wood skirting with NC lacquer finish</p>	Sft.	225		



	<p><b>Glazing</b> 6 mm thick clear float glass fixed with continuous steam beech wood glazing beads of approved shape (finished 0'-1 1/4" x 0'-1") all round polished and coated with NC lacquer finish. The rate should also include cost for decorative itching on one side of the glass</p> <p><b>Hardware</b> Providing &amp; Fixing door closer &amp; mortise lock with 4" kabja &amp; other misc. hardware.</p>			
7.0	<p><b>FULL HEIGHT NON GLAZED PARTITION:</b> Providing and fixing full height wooden partition (ups &amp; stationary, loan dept. cabin) with frame of 2"x2" (finished size) seasoned hard wood member at max intervals of 1'-6" x 1'-6" c/c with provision of bigger at skirting, fixing to the ceiling, slab, beams etc including the door of size 3'-0"x7'-0". All woodwork to be treated with 1st quality anti termite paint and should be covered with 12 mm thick ply Board of Approved make finished by 1.0 mm thick laminate of approved.</p>	Sft	126	
8.0	<p><b>LOW HIGHT PARTITION WITH FLAP DOOR</b> Made out of Sal Wood /ghamar Wood frame 0'-2" x 0'-2" and 12 mm thick BWR plywood on its both sides finished with 1 mm thick laminate pasted with fevicol Edges of the top gate finished with teak wood beading polished in natural shade. The gate shall be provided with Oxidized M S hinges and door springs. Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect. Size:</p>	Sft	12	
9.0	<p><b>CASH COUNTERS AND SINGLE WINDOW</b> Made out of 19 mm thick BWR plywood for working top keyboard shelf and vertical sides of counter and stronger unit front apron of 19 mm thick BWR ply with four 1'-6" wide drawers (of equal height) on the right side shall be provided. Division shall be made in appropriate sizes in drawers to store currency notes of different denominations and different sizes. Customer hand rest 1'-3" wide and 1'-0" high made of 12 mm thick BWR plywood for the vertical surface and the top shall be provided. 3/4" thick polished jet black granite with beveled edges shall be provided above the working top and customer top. 19 mm thick and 2'-0" wide</p>	Rft	10	



	<p>plywood of approved make shall be provided 0'-3" above floor level and across the counter for CPU shelf and foot rest. All exposed visible surfaces of counter like working top, front apron, drawers etc shall be finished with 1 mm thick laminate of approved make and shade. The key board shelf shall be 2'-0" x 2'-0" size and provided with teak wood beading polished natural. (0.8mm thick) laminates on the inner side. Height and width of the writing top shall be 2'-6". Height of the customer hand rest shall be provided with Godrej Multipurpose locks, metal telescopic channels and S S finished oxidized handles(0'-3") and hardware Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect</p>				
10.0	<p><b><u>OFFICERS COUNTERS (EXECUTIVE TABLES)</u></b></p> <p>Made out of 19 mm thick BWR plywood for working top keyboard shelf and vertical sides of counter and stronger unit front apron of 19 mm thick BWR ply with four 1'-6" x 0'-6" wide drawers (clear dimension) removable shelf and cupboard with shutter on the right side shall be provided. The writing top shall be provided with <math>\frac{3}{4}</math>" thick polished jet black granite with beveled edges shall be provided above the working top and customer top. 19 mm thick and 2'-0" wide plywood of approved make shall be provided 0'-3" above floor level and across the counter for CPU shelf and foot rest. All exposed visible surfaces of counter like working top, front apron, drawers cupboard fascia etc shall be finished with 1 mm thick laminate of approved make and shade. The key board shelf shall be 2'-0" x 2'-0" size and provided with teak wood beading polished natural. (0.8mm thick) laminates on the inner side including supply and fixing of sliding keyboard of approved make. Height and width of the writing top shall be 2'-6" and 2'-9" each The Drawers and shutters shall be provided with Godrej Multipurpose locks, metal telescopic channels and S S finished oxidized handles(0'-3") and hardware Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect</p> <p>Officer (5'-0" x 2'-6" x 3nos.),</p> <p>Low ht. storage = 20'x2'6"+9'x2'6"+3'x2'6"</p>	each	3		
		sft	75.4		



11.0	<b><u>CASH CABIN PARTITION</u></b>	<p>Made out of 2" x 2" (clear size) Sal wood chill wood members placed at not more than 2'-0" distance both ways and 12 mm thick BWR ply board of approved make finished with 1 mm thick laminate of approved make and shade on both sides. Skirting and bands shall be provided in the partition as directed by Architect</p> <p>An opening of 8" x 4" at 3'-0" height with 8" x 8" tray made of 12 mm thick BWR plywood of approved make finished with 1 mm thick laminate of approved make and shade on all four sides shall be provided wherever required</p> <p>The partition shall have aluminum grill # 009/101 of approved make and powder coated in approved color in wooden frame from 3'-9" height to 7'-0" height</p> <p>A Door shutter made of same specification and finished with 1 mm thick laminate of approved make and shade shall be provided in the partition with Godrej make S S finished cylindrical lock S S heavy duty hinges and door closer of approved make shall be provided in the shutter.</p> <p>Size: 8'0"x8'0"x1Nos. , 10'0"x8'0"x1 Nos. ,4'6"x8'0" [include door]</p> <p>Door size : 2'6"x7'0"x 2Nos.</p>	Sft.	310		
12.0	<b><u>FRONT PARTITION FOR CASH CABIN AND SINGLE WINDOW</u></b>	<p>12 mm thick clear float glass partition from top of the customer hand rest to 6'-9" height fixed with the side wooden partition. A semicircular opening (0'-8" dia) and 0'-2" wide slit shall be provided along with aluminum mesh in the partition as directed by the Architect</p>	Sft.	65		
13.0	<b><u>FRONT PARTITION FOR COUNTERS</u></b>	<p>12 mm thick clear float glass partition along with 1'-0" wide 12 mm thick clear float glass horizontally placed above it shall be provided in front of the clerical counters. 0'-2" wide slit shall be provided in the partition at the bottom. Total height of partition along with the horizontal glass member and slit is 1'-3". The glass partition shall be fixed with 0'-2" x 0'-2" wooden posts 1'-3" high and finished with 1 mm thick laminate of approved make and shade</p> <p>Size: 20'0"x1"x1nos</p>	Sft	15		



14.0	<b><u>ROLING SHUTTER BOX.</u></b> Providing and fixing Rolling shutters boxes made out of 2" x 1 1/2" size teak wood frame work. 19 mm thick BWR plywood open able door etc, complete with enamel paint finish of approved quality & shade as per instruction 9'x1'6"x2Nos. , 9'x2'0"x1Nos. , 2'0"x1'6"x2Nos.	Sft	0		
15.0	<b>Providing Factory made Aluminum Main Entrance Door of</b> INDAL / Jindal sections minimum section thickness of 2.5 mm all complete with swing door, fixed portion all 12 mm thick glass, colored anodized / powder coated as per standard approved sections ,with logo of UCO BANK made with etching on glass neatly. All complete with all necessary hardware and fittings, including floor springs, door lock etc. Door size- 7'x3' ATM DOOR- 3'0"x7'0"	Sft	90		
		sft	0		
16.0	<b><u>CHEQUE DROP BOX</u></b> Providing and fixing one suggestion box, made with 12 mm ply as per standard design and specification of the Bank fully complete with lock, lettering on top etc.	Each	1		
17.0	<b>Providing and fixing Cheque writing / slip rack projected/</b> supported from wall 6'-0" x 1'-3" and a C T as per design with suggestion box first aid box.	Each	1		
18.0	<b><u>SUGGESTION BOX</u></b> Providing and fixing one suggestion box made with 12 mm ply as per standard design and specification of the Bank fully complete with enamel painting, lock, lettering on top etc	Each	1		
19.0	<b><u>ALLUMINIUM JALI</u></b> Providing and fixing aluminum JALI FRAMING and hardware complete in all respect..	Sft	100		
20.0	<b>BLINDS:</b> Providing and fixing LUXAFLEX/VISTA LEVELOR brand Venetian Providing and fixing LUXAFLEX/VISTA LEVELOR brand Venetian blinds with 4" wide woven fabric coated blinds mechanism housed in head rail 1" wide high extruded from aluminum and louvers to be hung extruded from aluminum and louvers to be hung on superior quality runners with attached stainless steel spacer to obtain over lapping of 15 mm between the louvers	sqft	0		



21.0	<b>FALSE CEILING</b> Providing and fixing it true horizontal level false ceiling grid using hot galvanized steel section exposed surface chemically clean capping pre finished in baked pollster paint silhouette type main TEE size of 15x41x0.33 mm at every 1200 mm c/c [use 2'0"x2'0" tile] make -ARMSTRONG, SAINT GOBINS,USG BORAL	Sqft	0		
22.0	<b>ACP CLADDING[ FOR ATM]</b> Providing and fixing in position ACP sheet of standard make [Aludecor, Alstrong or equivalent approved by the bank with its necessary accessories aluminum section 600mmx600mm Designing, fabricating, testing, installing and fixing in position Curtain Wall with Aluminum Composite Panel Cladding, with open grooves for linear as well as curvilinear portions of the building , for all heights and all levels etc.	SQFT	0		

