

सम्मान आपके विश्वास का

Honours your trust

UCO BANK, ZONAL OFFICE, 1st Floor, Plot No-22, Jail Road, Arera Hills BHOPAL-462027

DATE-26.08.2015

Empanalment of vendors for supply & New Installation of CCTV and Annual Comprehensive Maintenance Contract of existing CCTV systems at the bank branches under Bhopal Zone.

Applications are invited from reputed Companies /Firms for Supply & Installation of CCTV in 05 no of branches (Seoni, Chindwar, Sidhi, Umaria & Jatkhedi (Bhopal) and Annual Comprehensive maintenance Contract of existing CCTV systems in 80 branches/offices under Bhopal Zone of UCO Bank, Madhya Pradesh, functioning in the districts Anuppur, Ashok Nagar, Balaghat, Betul, Bhind, Bhopal, Chaterpur, Chindwara, Damoh, Datia, Dindori, Guna, Gwalior, Harda, Hosangabad, Mandla, Morena, Narsinghpur, Panna, Raisen, Rajgarh, Sagar, Sehore, Seoni, Sheopur, Shivpur, Sidhi, Singhrauli, Tikamgarh, Umaria, Vidisha. Only those companies and firms who fulfill following eligibility criteria will be considered for empanelment:-

- a) Reputed service providers specializing in providing and installation of CCTV Systems for at least last 5 years in the field as on 01.10.2015.
- b) Ability to undertake the work and maintenance of all branches throughout the Bhopal zone.
- c) Ability to provide CCTV systems as per technical specifications available at Appendix-III & IV of this advertisement.
- d) Ability to commence service within 15 days from date of placement of order.
- 2. The vendor should meet the eligibility criteria, General requirements, and other mandatory Requirements as per details available at Appendix- I & II of this advertisement.
- 3. The system should meet with technical specification and details given in Appendix- II & III.
- 4. Empanelment of vendors may be restricted to maximum 10 vendors in accordance with merit towards fulfillment of eligibility criteria in a descending order specified in Appendix-I & II and fulfillment of technical specification compliance given in Appendix-III & IV.
- 6. 10% of the payment will be retained by bank for 1 Year (warranty period) from the date of Installation as defect liability period money.
- 7. The vendor has to give an undertaking that they will give a performance Bank guarantee of Rs- one lakh for five years for the AMC of existing CCTV systems installed at Branches of Bhopal Zone, and this performance guarantee will be in vogue in case of new CCTV installations and their AMC after the expiry of warranty period of one years, and this undertaking has to be enclosed with the eligibility bid.
- 8. The vendor has to give an undertaking that
 - I) The hard disk they will supply is a surveillance hard disk
 - II) DNS software & remote health monitoring software has to be provided free of cost by the Vendor.
 - III) The above stated both the undertakings have to be enclosed with the eligibility bid.
- 9. Applications are to be sent to the undersigned in two sealed covers super scribed as Part-I (eligibility bid & technical bid) & Part-II (financial bid) with vendor's complete address and contact number on or before 15.00 hrs on 12TH September 2015 as under:

- Part I. (a) Eligibility bids- to include profile of the company.
 - List of major existing clients, registered number and sales tax details etc. as per Appendix-I
 & II point wise. Attach document wherever required.
 - EMD shall be Rs-25,000/-(Twenty five thousand only) to be deposited along with tender document through Demand draft, Bankers Cheque or Pay Order in favour of UCO Bank, Zonal Office, Bhopal.
 - (b) Technical bids -to meet the technical specification:
 - Compliance of technical specification of CCTV Systems given in Appendix III, IV, IVA, IVB, IVC point wise.
 - 2) The system and all the parts should meet with standard stipulated as mentioned in technical specification.
 - **Part-II** Financial bids should be: Net rates (inclusive of all taxes, levies, installation, handling & maintenance charges) as mentioned in **Appendix V**.

(Vendors may be asked to submit Copy of certification of equipment i.e. UL/CE/FCC, (MAF) copy of document of authorization from manufacturer to Indian dealers and from Indian dealer to supplier undertaking that the cards supplied are original and from OEM/distributor)

- 10. EMD shall be Rs-25,000/-(Twenty five thousand only) to be deposited along with tender document through Demand draft, Bankers Cheque or Pay Order in favour of UCO Bank, Zonal office, Cuttack. EMD is liable to be forfeited in the event of:
 - i. Revocation of the tender or increasing the rates after opening of the tender and before the expiry of the validity of tender.
 - ii. Refusal of the vendor/Contractor to execute the agreement or not complying with the contractual terms & conditions after awarding of contract.
- 11. The interested vendors may obtain the tender papers from the under mentioned bank address, or can be downloaded from our banks website www.ucobank.com. For any other queries, vendors may contact the Security Officer of this office on working days between 11 A.M. to 4 P.M.
- 12. Part-I (a) Eligibility bid shall be opened on <u>14th September 2015 at 12.00 hrs</u> and Part-I (b) Technical bid will be opened only if Bank is satisfied with Part-I (a). Opening of Technical bid & Live demonstration of the system will be held on 16th September 2014 at 11.00 hrs. Part-II (Financial bid) of empanelled vendors will be opened on <u>18th September 2015 at 15.00 hrs</u>, only if bank is satisfied with Part-I (a), Part-I (b) and satisfactory live demonstration of the system as per technical specification.
- 13. Bank reserves the right to reject any/all bids without assigning any reason thereto.
- 14. Bank is not responsible for late receipt of application or its damage in transit.
- 15. Any dispute arising in this matter will be settled in the jurisdiction of Bhopal, Madhya Pradesh.

Deputy General Manager & Zonal Head Zonal Office, UCO Bank building, 1st Floor, Arera Hills, Jail Road, Bhopal-462027 (MP)

E-mail: zo.bhopal@ucobank.co.in

Phone No **0755-4046020**

ELIGIBILITY CRITERIA OF VENDORS FOR SUPPLY, INSTALLATION AND ANNUAL COMPREHENSIVE MAINTENANCE OF CCTV SYSTEM

- 1. Vendor providing CCTV systems should have been in business for the last five years as on 01.10.2015.
- 2. Vendor providing CCTV system should have adequate technician and local service center at Bhopal/Gwalior to attend and repair the complaint and breakdown within 24 hour in Bhopal city & and nearby areas i.e. within a radius of 50 kms from Bhopal city and 48 hours in the district of rest of the area Give the exact number of technician working in your concern.
- 3. Vendor should have a Certificate of Registration with Registrar of Companies or Registrar of Firms or have a letter of proprietorship.
- 4. Vendor should provide the latest Income Tax Assessment Order and PAN/ TAN Number.
- 5. Vendor should provide the latest Audited Balance Sheet Preceding 3 Years.
- 6. Vendor should provide total annual turnover for last 3 years.
- 7. Vendor should provide name and address of banker with solvency certificate not older than one year.
- 8. Vendor should have a local Office in the state of Madhya Presdesh preferably at Bhopal/Gwalior. Give postal address and contact number.
- 9. Vendor should provide telephone number of local office and service center with address under Bhopal/Gwalior.
- 10. Vendor should be registered under the appropriate authority for service tax.
- 11. The vendor has to give an undertaking that they will give a performance Bank guarantee of Rs. one lakh for five years for the AMC of existing CCTV systems installed at Branches of Bhopal Zone, and this performance guarantee will be in vogue in case of new CCTV installations and their AMC after the expiry of warranty period of ONE years.
- 12. The vendor has to give an undertaking that
 - I) The hard disk they will supply is a surveillance hard disk
 - II) DNS software & remote health monitoring software has to be provided free of cost by the Vendor.
- 13. Vendor should have supplied CCTV system to Nationalized/ Private Banks in the state of Madhya Pradesh.
- 14. The vendor has to give an undertaking that, they are willing to carry out the AMC job of existing CCTV systems installed earlier and the AMC job of new CCTV systems to be installed (after the expiry of warranty period of ONE years), at a uniform price for both the AMCs.
- 15. The vendor has to provide the Manufactures authorization form (MAF) from the OEM and Back to Back support certificate from the dealer/distributor in India i.e. for HIKVISION: M/S Prama Hikvision India Pvt Ltd and for DAHUA: from M/S Aditya Infotech Ltd.
- 16. The Hard Disk capacity to be calculated for 90 days storage capacity. D1 quality footage with 700TVL camera, recording quality with 1024 bit rate & 25fps will require approximately 6 TB HDD for 90 days recording.

General Requirements			
Vendo	rs compliance		
1	Warranty for One year		
2	Post warranty comprehensive AMC for 5 years		
3	Support for retrieval of image for dispute resolution at no additional cost		
4	Necessary software for retrieval of Data from the DVR Hard disc at no additional cost		
5	Necessary software for retrieval of data from the DVR Hard Disc on		
6	UL,CE and FCC certification for imported parts/components and ISI for indigenous parts/components		

Date

Signature and Seal of the vendor

MAKE & MODELS OF CCTV COMPONENTS APPROVED BY UCO BANK HEAD OFFICE:-

DVRs:-

SI	Product Name	Models	Make
1	32 Channel DVR	DS 8132HWSI-SH	HIKVISION
2	16 Channel DVR	DS 8116HWI-ST	HIKVISION
3	08 Channel DVR	DS 7308HWI-SH	HIKVISION
4	04 Channel DVR	DS 7304HWI-SH	HIKVISION
5	04 Channel ATM DVR	DS-8104HWLI-ST	HIKVISION

SI	Product Name	Models	Make
1	32 Channel DVR	DH-DVR3204HF-S1	DAHUA
2	16 Channel DVR	DH-DVR1604HF-S1	DAHUA
3	08 Channel DVR	DH-DVR0804HF-L1	DAHUA
4	04 Channel DVR	DH-DVR0404HF-S1	DAHUA
5	04 Channel ATM DVR	DH-DVR0404 AH-V(D)	DAHUA

CAMERAS:-

SI No	Product Name	Models	Make
1	DOME IR, VERIFOCAL VANDALPROOF CAMERA	DS-2CC52A1P-VPIR2	HIKVISION

2	BULLET IR, VERIFOCAL, WEATHER PROOF CAMERA	DS-2CC11A2P-VFIR3	HIKVISION
3	PINHOLE CAMERA	DS-2CC51A2P(N)-DG1	HIKVISION

SI No	Product Name	Models	Make
1 2	DOME IR, VERIFOCAL VANDALPROOF CAMERA BULLET IR, VERIFOCAL, WEATHER PROOF CAMERA	DH-CA-VMS35V2N3-V2 DH-CA-BTS35V2A4-V3	DAHUA DAHUA
3	PINHOLE CAMERA	DH-CA-P470CP-AV3	DAHUA

Monitor: LG/SAMSUNG

Note:-

- 1. Henceforth, only the above mentioned Make & Model of CCTV and its components to be installed in the branches.
- 2. You will provide the Manufactures authorization form (MAF) from the OEM and Back to Back support certificate from the dealer/distributor in India i.e. for **HIKVISION**: **M/S Prama Hikvision India Pvt Ltd** and for **DAHUA**: from **M/S Aditya Infotech Ltd**.
- 3. The Hard Disk capacity to be calculated for 90 days storage capacity. D1 quality footage with 700TVL camera, recording quality with 1024 bit rate & 25fps will require approximately 6 TB HDD for 90 days recording.

Date

Signature and Seal of the vendor

Appendix -A

Date:

Manufacturer's Authorization Form (MAF)

NO	darea
Zonal Manager, UCO Bank, Zonal Office	
Dear Sir,	
Subject:	
manufactures of hereby authorise M/s	who are established and reputable having factories at and do (Name and address of Vendorn, negotiate and conclude the contract with you against the
and the contract for the equip by the above firm and confirm	rantee and warranty as per terms and conditions of the RFP ment and services offered against this invitation for RFP offer that back to back Spare & Skill Arrangement has been madefor providing support services to UCO Bank
Yours faithfully,	
Authorized Signatories (Name & Designation) Date:	
For and on behalf of M/s (Name of manufactures)	
should be signed by a co	ould be on the letterhead of the manufacturing concern and impetent person of the manufacturer. offered for which the vendor is not an OEM, should be

Place:

(To be submitted by OEM/Distributor)

No	Date:
Zonal Manager, UCO Bank, Zonal Office	
Dear Sir,	
Subject:	
Standalone DVR based (components / parts / ass	who are established and reputable of having factories/Office at certify that all the components / parts / assembly / software used in the CCTV Systems i.e. DVR, Camera, Monitor etc, are original with new embly / software and that no refurbished / duplicate / second hand nbly / software are used or would be used.
services, offered against t	I guarantee and warranty as per terms and conditions of the RFP and his invitation by us. We also confirm that back to back spare & skill de with for providing support services to UCO Bank under this contract.
Yours faithfully,	
Authorized Signatories (Name & Designation) Date:	
For and on behalf of M/s (Name of manufactures)	
•	should be on the letter head of OEM/Distributor and should be authority of the agency.
Date:	

APPENDIX - 'III'

SI	TECHNICAL SPECIFICATION FOR 8,16 & 32 CHANNELS STANDALONE	
No	<u>DVR</u>	COMPLIANCE
	Operating System: Embedded Linux .	
2	DVR should be system embedded with H.264 video compression	
	algorithm.	
3	Video Frame rate/speed:- 8/16/32 Channel DVR :-240/480/960fps-	
	NTSC; 200/400/800 fps -PAL.	
4	Simultaneous Live viewing, Remote viewing, Backup, recording and	
_	Playback functions: Pentaplex .	
	Display on line resolution / Preview resolution 976*576 PAL	
	Multiple Viewing Option (VGA/BNC).	
7	Video Inout / Loop out: 8/8, 16/16 & 32/32	
8	Video Output: 1 composite, 1 HDMI, 1 VGA, 1 Spot.	
9	Audio in / out: minimum 4/1	
	Video display:-for 8 CH-1,4,6,8; for 16 CH-1,4,8,13,16; for 32 CH-1,4,8,10,13,16,25,32	
10	Recording Rate: PAL: Real Time (25 fps per channel),WD1 with all	
	Channels recording and playback both. Player software auto	
	download with backup on DVD.	
11	System should be robust and capable of working in 24*7 environment.	
	System should be scalable / upgradeable.	
	Storage Media: Built in Recording up to 90 days in real Time	
L	(25 FPS per channel)	
14	Provision for minimum 4 SATA slots for 3 HDD + DVD – RW (each	
	SATA slot should support upto 4 TB HDD capacity).For 16/32 Channel :	
	8 SATA slots	
	Data storage for 90 days. Data recycling on FIFO basis.	
	Network Interface: Ethernet (RJ-45, 10/100 Base-Tx), External	
	Model Via RS-232 Port, RS 485 port.	
	Support Multi Zone Motion Detection.	
18	Support multilevel Pass Word For Operation, setup and remote	
10	Access.	
19	Support Waterproof marking to ensure tamper proof recording	
00	of images. Support tamporing detection alarm function to indicate	
	Support tampering detection alarm function to indicate	
	tempering of DVR / Cameras. Visual indication for local faults, disc full, malfunction etc.	
21	Support video signal loss alarm. System should do health check	
_	of all cameras.	
22	Support position configurable to OSD and LOGO.	
	Support Real Time and Motion Based Recording.	
	Support HDD Sleep Mode.	
	Support FAT 32 File System.	
	Support USB flash dish, USB DVD-RW for backup with built in DVD-RW.	
27	Support playback in various modes fast ,slow ,pause, forward,	
_	backward, frame-by-frame.	
	Support TCP, UTP, RTP, PPPOE, Multicast, DHCP etc.	
29	Connectivity: Provision for ADSL, PSTN, Leased Line, Broad Band.	

30	Remote play back, Download the recorded files in DVR.	
31	Remote viewing through Mobile phones / and through any	
	other PC with IP (RHMS).	
32	System should have file player software so that back up can be	
	auto played on any PC Using Windows Media Player.	
33	Vender Should provide Central Monitoring Station (CMS)	
	Software free of cost and this software should be compatible to	
	CMS software of third party, as well. The system should be	
	capable of running Remote Health Monitoring System.	
34	Power AC-100/240 V & 50 / 60 Hz.	
35	DVR housing with wall mounting 4U rack and tamperproof locking	
	arrangement.	
36	System Should carry UL,FCC & CE certification.	
37.	HDD Inbuilt with DVR-Seagate/Western Digital Make, Surveillance	
	Hard Disk series (AV series SvI/ SV-35.3 SvI)	
38.	Warranty: One Year	

	General Requirements	
1	Warranty for one year	
2	Post warranty AMC for 5 years	
3	Support for retrieval of images for dispute resolution at no additional cost	
4	Necessary software for retrieval of Data from the DVR Hard Disc on	
5.	Open platform with sharing of information on DVR Software Disk Kit (SDK) for CMS by any third party	
6.	UL,CE and FCC certification for imported parts/components and ISI for Indigenous parts/components	

Date

Signature and Seal of the vendor

APPENDIX-' IV'

VARI-FOCAL DOME IR CAMERA VANDALPROOF

SL.	Vari focal dome IR Camera	Specifications	Vendors Compliance Y/N
1	Pick up Element	1/3" Super HAD-II CCD	
2	Effective Pixel	PAL: 976x582, NTSC 976x494	
3	Scanning System	2:1 interlace	
4	Sync System	Internal / External Line Lock	
5	Resolution	700 TV lines	
6	Sensitivity	0.01 lux	
7	S/N Ratio	MORE THAN 52 db. (AGC Off, F1.2)	
8	Electronic shutter	Auto: 1/50 (60) to 1/120,000sec	
9	Output	1Vpp Composite video output, 75 Ohm	
10	Lens Type	2.8 – 10 mm Auto Iris DC lens and IR corrected	
11	IR Range	20-30 mtrs	
12	Day/Night	True day/night	
13	Auto White Balance	Auto	
14	Back Light Compensation	OFF/ON SELECTABLE	
15	Automatic Gain Control	OFF/ON SELECTABLE	
16	Flicker less Mode	OFF/ON SELECTABLE (NTSC 1/100; PAL 1/200)	
17	Operating Temperature	10 to 50° C / 30 – 90% RH	
18	Power supply	12VDC/24VAC Auto Detectable	
19	Power consumption	Less than 4 watts with LED ON	
20	Working Condition 24 * 7	Support	
21	Product warranty	1 year minimum	
22	Certification	UL,CE & FCC	

APPENDIX-'IV'A

VARI-FOCAL BULLET IR CAMERA- WEATHERPROOF

SL.	Vari focal dome IR Camera	Specifications	Vendors Compliance Y/N
]	Pick up Element	1/3" Super HAD-II CCD	
2	Effective Pixel	PAL: 976x582, NTSC 976x494	
3	Scanning System	2:1 interlace	
4	Sync System	Internal / External Line Lock	
5	Resolution	700 TV lines	
6	Sensitivity	0.01 lux	
7	S/N Ratio	MORE THAN 52 db. (AGC Off, F1.2)	
8	Electronic shutter	Auto: 1/50 (60) to 1/120,000sec	
9	Output	1Vpp Composite video output, 75 Ohm	
11	Lens Type	2.8 – 10 mm Auto Iris and IR corrected	
12	IR Range	30-40 mtrs	
13	Day/Night	True day/night	
14	Auto White Balance	Auto	
15	Back Light Compensation	OFF/ON SELECTABLE	
16	Automatic Gain Control	OFF/ON SELECTABLE	
17	Flicker less Mode	OFF/ON SELECTABLE (NTSC 1/100; PAL 1/200)	
18	Operating Temperature	10 to 50° C / 30 – 90% RH	
19	Power supply	12VDC/24VAC Auto Detectable	
20	Power consumption	Less than 4 Watt with LED ON	
21	Working Condition 24 * 7	Support	
22	Product warranty	1 year minimum	
23	Certification	UL,CE&FCC	

APPENDIX-'IV'B

PIN HOLE CAMERA

SL.	Vari focal dome IR Camera	Specifications	Vendors Compliance Y/N
1	Pick up Element	1/3" Super HAD- IICCD	
2	Effective Pixel	PAL: 976x582, NTSC 976x494	
3	Scanning System	2:1 interlace	
4	Sync System	Internal / External Line Lock	
5	Resolution	700 TV lines	
6	Sensitivity	0.01 lux	
7	S/N Ratio	MORE THAN 52 db. (AGC Off, F1.2)	
8	Electronic shutter	Auto: 1/50 (60) to 1/120,000sec	
9	Output	1Vpp Composite video output, 75 Ohm	
11	Lens Type	3.7 mm or less, wide angle	
12	Day/Night	Auto	
13	Auto White Balance	Auto	
14	Back Light Compensation	OFF/ON SELECTABLE	
15	Automatic Gain Control	OFF/ON SELECTABLE	
16	Flicker less Mode	OFF/ON SELECTABLE (NTSC 1/100; PAL 1/200)	
17	Operating Temperature	10 to 50° C / 30 – 90% RH	
18	Power supply	12VDC/24VAC Auto Detectable	
19	Working Condition 24 * 7	Support	
20	Product warranty	1 year minimum	
21	Certification	UL,CE &FCC	

Date

Signature and Seal of the vendor

APPENDIX-'IV'C

Item No	Item Name	Specifications	Vendors Compliance Y/N
A	Hard Disk Drive	Surveillance Hard disc Drive	.,
	Seagate/Western Digital (Surveillance HDD)	32~64 MB Cache, 3 MB~6MB per second data transfer rate.	
В	MONITOR (Samsung/LG)	LCD with TCO 03 or equivalent certification	
	Screen Size	19", 24" & 32 " diagonal TFT LCD/LED	
	Make	Samsung/LG	
	Video	PAL/NTSC color composite	
	Resolution	1280*1024/ 1368*720 Pixels @	
		60~85 Hz Refresh Rate, True Colour (32 Bit)	
	Power input	90-260VAC or 121 V DC	
	Viewable Angle	140° H, 130° V	
С	Cable- Video		
	Category	Co Axial RG 6	
	Type	Unnarmored	
	Capacitance	53 +/- 3 Ohms	
	DC resistance inner conductor	8.5 Ohms / KM	
	Di-electric strength	10 KVA AC Mains	
	Di electric material	Polythene (PE), 7.1 mm dia	
	Insulation resistance	50 M Ohms/KM	
	Nominal Impedance	75 Ohms	
	Minimum bending radius	55 mm	
	Acceptable Quality	Make – Finolex, Polycab, Jaitex	
D	Cable- Power	Unarmored	
	Category	2 Core power cable, FRLS	
	Type	2 core x 0.75 sq mm	
	Acceptable type	ISI Marked (IS-694, 1990)	
		Make – Finolex, Polycab,	
	Insulation	PVC Insulated	
E	PVC Conduits for cabling.		
	Specification	20 mm dia	
	Acceptable Quality	ISI Marked, Make – Precision or equivalent	
			i de la companya de

IMPORTANT:- All imported products, e.g. Cameras, DVRs should carry quality certification i.e. CE , FCC and UL. (Copies to be enclosed) and all Cable and PVC conduit i.e. ISI Marked.

N.B. rest specifications of cameras will be as specified in Appendix 'C to C2'

4 C	H ATM DVR- Technical Sp	ecification
1	Operating System	Embeded Linux
2	Video Compression	Embeded with H.264 Video Compression Algorithm
3	No of Video channel	4
4	System features	Simultaneous Viewing, record, play Back, back up & Network
5	Display Resolution	BNC- 704X576 (PAL), 704X480(NTSC)
6	Frame Rate	PAL-D1 quality
7	Video Input	4 Channel
8	Video Output	1BNC,1VGA
9	Storage	Hard Disc-90 days recording minimum
10	Record	Manual, Alarm, Motion Detection & Schedule
11	Support Function	Multi Zone Motion Detection, Multi level password protection
12	Content Control	Water Marking for authentic Video footage
12	Search	Date/Time, Logistic Event, Channel
13	Back up	USB/USB-DVD-RW
14	Remote Function	Mobile view, Back up
15	HDD	02 slots minimum
16	Built in display	7" minimum
17	Text Overlay	ATM POS for text overlay feature
18	Housing	ATM DVR cabinet with temper proof locking arrangement
15	Certification	CE,FCC & UL
	Camera Type & Location	n
1	Туре	Colour, Preferably IR Dome, if required may be Pinhole
2	Numbers	2, Minimum
3	Location	Camera should be installed in such a way that the camera view Should not cover key Pad, One camera outside and one inside the ATM room.
J	LOCUIIOIT	THE AIMTOUTH
	Camera Specification	
	IR Dome Camera,	
1	vandal proof	1/3" HAD-II CCD, 0.01 Lux, 700TVL, 3.6 mm Wide Angle fixed Lens
2	Pin Hole Camera	1/3" HAD CCD, in appropriate housing 0.01 Lux, 700TVL,
	ID levilled a grant array	3.7 mm Wide Angle fixed Lens
3.	IR bullet camera, weather proof	1/3" HAD-II CCD, 0.01 Lux, 700TVL, 3.6 mm Wide Angle fixed Lens

Appendix-V Financial Bid

	Appendix – V- Financial Bid	8 CHANNEL STANDALONE DVR	16 CHANNEL STANDALONE DVR
SN	TECHNICAL SPECIFICATION FOR 8&16 CHANNELS STANDALONE DVR	unit cost inclusive of all the applicable taxes, handling, delivery & installation charges	unit cost inclusive of all the applicable taxes, handling, delivery & installation charges
1	Operating System: Embedded Linux.		
2	DVR should be system embedded with H.264 video compression algorithm.		
3	Video Frame rate/speed:- 8 / 16 Channel DVR 240 / 480/960 fps-NTSC 200/400/800 fps-PAL.		
4	Simultaneous Live viewing, Remote viewing, Back up, , recording and Playback functions. Pentaplex		
5	Display on line resolution / Preview resolution 976*576 PAL		
6	Multiple Viewing Option (VGA/BNC).		
7	Video Inout / Loop out: 8/8 & 16/16		
8	Video Output: 1 composite, 1 HDMI, 1 VGA, 1 Spot.		
9	Audio in / out: minimum 4/1		
10	Recording Rate: PAL: Real Time (25 fps per channel), WD1 with all Channels recording and playback both. Player software auto download with backup on DVD.		
11	System should be robust and capable of working in 24X7X365 environment.		
12	System should be scalable / upgradeable.		

13	Storage Media: Built in Recording up to 90 days in real Time (25 FPS per channal)		
14	Provision for minimum 4 SATA slots for 3 HDD + DVD - RW (each SATA slot should upto 4 TB HDD capacity). For 16/32 channel: 8 SATA slots		
15	Data storage for 90 days. Data recycling on FIFO basis.		
16	Network Interface: Ethernet (RJ-45, 10/100 Base-Tx), External Model Via RS-232 Port, RS 485 port.		
17	Support Multi Zone Motion Detection.		
18	Support multilevel Pass Word For Operation, setup and remote Access.		
19	Support Waterproof marking to ensure tamper proof recording of images.		
20	Support tampering detection alarm function to indicate tempering of DVR / Cameras. Visual indication for local faults, disc full, malfunction etc.		
21	Support video signal loss alarm. System should do health check of all cameras.		
22	Support position configurable to OSD and LOGO.		
23	Support Real Time and Motion Based Recording.		
24	Support HDD Sleep Mode.		
25	Support FAT 32 File System.		
26	Support USB flash dish, USB DVD-RW for backup with built in DVD-RW.		
27	Support playback in various modes fast, slow, pause, forward, backward, frameby-frame.		
28	Support TCP, UTP, RTP, PPPOE, Multicast, DHCP etc.		
29	Connectivity: Provision for ADSL, PSTN, Leased Line, Broad Band.		
30	Remote play back, Download the recorded files in DVR.		

31	Remote viewing through Mobile phones / and through any other PC with IP (RHMS).			
32	System should have file player software so that back up can be auto played on any PC Using Windows Media Player.			
33	Vender Should provide Central Monitoring Station (CMS) Software free of cost and this software should be compatible to CMS software of third party, as well. The system should be capable of running Remote Health Monitoring System.			
34	Power AC-100/240 V & 50 / 60 Hz.			
35	DVR housing with wall mounting bracket and tamper proof locking arrangement.			
36	System Should carry UL/FCC/CE certification.			
37	HDD Inbuilt with DVR- Seagate/western Digital Make, Surveillance Hard Disk series (AV series SvI/SV- 35.3SvI)			
38	Warranty: One Year			
39	Post warranty AMC for 5 years			
40	Support for retrieval of images for dispute resolution at no additional cost			
	TOTAL COST OF DVR PER SYSTEM			
II	TECHNICAL SPECIFICATION FOR CAMERAS		Cost inclusive te per unit)	of
1	Vari- Focal Dome IR Camera - With specification of appendix IV			
2	Vari- Focal Bullet IR Camera- Weather Proof – With specification of appendix IV A			
3	PIN Hole Camera – With specification of appendix IV B			

1				ı	
	Note: All Cameras Should				
	carry UL/FCC/CE certification				
	& are to be supplied with				
	associated mounting bracket				
	and housing				
III	TECHNICAL SPECIFICATION				
	FOR MONITOR- With			Unit (Cost inclusive of Tax
	specification of appendix				
-	IV C				
1	LED 19", 24", 32" inch size,				
	model LG/Samsung(Rate per				
1) /	unit)				
IV	TECHNICAL SPECIFICATION FOR CABLING			Unit (Cost inclusive of Tax
_					
]]	RG 6 video coaxial cable per				
	meter (Rate per running				
	meter) (Brand Polycab)				
2	Two core, FRLS, 2 core X 0.75				
	sq mm per meter(Rate per				
	running meter) (ISI Marked, I-				
	694,1990, Brand- finolex,				
	Polycab)				
3	PVC conduits for cabling-				
	200 mm dia (ISI marked)				
	Make precision or equivalent-				
	per meter-(Rate per running				
4	meter)				
4	Price per running meter of all				
	the above stated three items				
			Cost inclusive of all		Cost inclusive of all
			taxes & charges (No		taxes & charges (No
	AMC -CONDITIONS		separate charges for		separate charges for any kind of spare parts
V	(COMPREHENSIVE AMC FOR 5		any kind of spare parts including Power		including Power supply,
	YEARS)		supply, Mother Board,		Mother Board, Hard disk,
			Hard disk, DVR, PCB,		DVR, PCB, Cameras will
			Cameras will be paid)		be paid)
	AMC Comprehensive (all				
	the spare parts cost				
	included, including power				
	supply, Mother board, Hard				
	disc, PCB, Complete DVR				
	unit, Cameras etc.) during				
	AMC period no separate				
	charges for any kind of spare				
,	parts will be paid. AMC for				
1	the above configuration for				
	five years and the rate				
	quoted for one year per				
1					
	branch for 4/8/16 channel	ļ			
	branch for 4/8/16 channel				
	branch for 4/8/16 channel CCTV system. The AMC				
	branch for 4/8/16 channel CCTV system. The AMC charges quoted by the				
	branch for 4/8/16 channel CCTV system. The AMC charges quoted by the vendor will also be				

	installed at various branches of Bhopal Zone.	
VII	Mention Service Centers/Office in the Bhopal/Gwalior(Specify City/town)	
VIII	Incase of refurbishing & shifting Relocation charges per Branch for 04,08,16 Channel system	

NOTE: ALL ABOVE MENTIONED ITEMS e.g. CAMERAS, DVRs SHOULD CARRY QUALITY CERTIFICATION I.E. CE, FCC AND UL (COPIES TO BE ENCLED) AND ALL CABLE AND PVC CONDUIT I.E. ISI MARKED

Seal

Date

(Signature of the tenderer/Vendor)

	Annexure - VI -Financial Bid	4 CHANNEL STANDALONE DVR FOR ATM	
SN I	TECHNICAL SPECIFICATION FOR 4 CHANNELS STANDALONE DVR	unit cost inclusive of all the applicable taxes, handling, delivery & installation charges	
1	Operating System: Embeded Linux		
2	Video compression :- Embeded with H.264 Video compression algorithm		
3	No of video channel-4		
4	System features:-Simultaneous viewing, record , Playback ,back up & Network.		
5	Display resolution:- BNC- 704x576(PAL),704x480(NTSC)		
6	Frame rate:-PAL- D1 quality		
7	Video Input :- 4 Channel		
8	Video Output: 1 BNC, 1 VGA .		
9	Storage:- Hard disc 90 days recording minimum		
10	Record:- Manual, alarm, Motion detection & Schedule.		
11	Support function:- Multi zone motion Detection, Multilevel password protection.		
12	Content control:- Water marking for authentic video footage		
13	Search:- date/Time, Loggistic event ,channel.		
14	Back up:-USB/USB-DVD-RW		
15	Remote function:-Mobile view ,Back up.		
16	HDD- 02 slots minimum		
17	Built in display 7" minimum		
18	Housing- ATM DVR cabinet with temper proof locking arrangement		
19	Certification:-CE/FCC/UL/-		
	DVR housing with wall mounting bracket and tamper proof locking arrangement for 4 Channel in Rs-	4 CHANNEL CCTV system DVR IN Rs	
	TOTAL COST OF EACH CCTV SYSTEM		
	Camera type & Location THE VENDOR	RATE QUOTED BY	
1	Type:-Colour, Preferebly C-mount, IR & Dome ,if required may be pin hole		
2	Number-2 Minimum		

3	Location:- Camera should		
	be installed in such a way		
	that the camera view		
	should not cover key pad,		
	one camera outside and		
	one inside the ATM room		
	Camera specification:-		RATE QUOTED BY
	THE VENDOR		
1	IR Dome camera:-1/3"		
	HAD-II CCD, 0.01 Lux, 700		
	TVL, 3.6 mm Wide Angle		
	fixed Lens vandal proof		
2	Pin Hole Camera- 1/3" HAD		
	CCD, in appropriate		
	housing 0.01 Lux, 700 TVL,		
	3.7mm wide Angle fixed Lens		
3	IR Bullet camera, weather		
	proof- 1/3" HAD CCD, in		
	appropriate housing 0.01		
	Lux, 700 TVL, 3.7mm wide		
	Angle fixed Lens		
III	TECHNICAL SPECIFICATION	DATE OLIOTED DV THE	VENDOD
	FOR MONITOR	RATE QUOTED BY THE	VENDOR
1	LED 19 inch size(Rate per		
	unit) (model LG/Samsung)		
IV	BUY BACK OF OLD CCTV	RATE QUOTED BY	
	SYSTEM ALONG WITH 4/8	THE VENDOR	
	CAMERAS & ACCESSORIES		
V	TECHNICAL SPECIFICATION		
	FOR CABLING		
1	RG 6 video coaxial cable		
	per meter (Rate per		
	running meter) (Brand		
	Polycab)		
2	Two core, FRLS, 2 core X		
	0.75 sq mm per meter(Rate per running meter) (ISI		
	Marked, I-694,1990, Brand-		
	finolex, Polycab)		
3	PVC conduits for cabling-		
	200 mm dia (ISI marked)		
	Make precision or		
	equivalent-per meter-(Rate		
	per running meter)		
4	Price per running meter of		
	all the above stated three		
\"	items		I
VI	AMO CONDITIONS		Cost inclusive of all taxes & charges
	AMC -CONDITIONS		(No separate charges for any kind of
	(COMPREHENSIVE AMC FOR 5 YEARS)		spare parts including Power supply,
	J IEARS)		Mother Board, Hard disk, DVR, PCB, Cameras will be paid)
1	AMO Commercial Commerc		Carrieras will be paid,
<u> </u>	AMC Comprehensive (all		

the spare parts cost included, including power supply, Mother board, Hard disc, PCB, Complete DVR unit, Cameras etc.) during AMC period no separate charges for any kind of spare parts will be paid. AMC for the above configuration for five years and the rate quoted for one year for 4/8/16 channel CCTV system. The AMC charges quoted by the vendor will also be applicable for the existing 04, 08, 16 Channel CCTV		
Systems installed at various branches of Bhopal Zone.		
Mention Service Centers/Office in the Bhopal/Gwalior(Specify City/town)		
In case of refurbishing & shifting Relocation charges per Branch/ATM for 04, Channel system		
	MS ARE TO BE SUPPLIED	AS PER SPECIFICATION GIVEN IN THE

NOTE: ALL ABOVE MENTIONED ITEMS ARE TO BE SUPPLIED AS PER SPECIFICATION GIVEN IN THE ABOVE TABLE AND INSTALLATION HAS TO BE COMPLETED AS PER REQUIREMENT OF EACH BRANCH.

Seal Date Signature of the tenderer/Vendor